




**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

(04.12.03)



Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03075076.4

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr.:
Application no.: 03075076.4
Demande no:

Anmeldetag:
Date of filing: 13.01.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Koninklijke Philips Electronics N.V.
Groenewoudseweg 1
~~5621 BA Eindhoven~~
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

A method of image registration and medical image data processing apparatus

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

G06T/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT SE SI SK TR LI

A method of image registration and medical image data processing apparatus

EPO - DG 1

13. 01. 2003

94

The present invention relates to image registration, and more particularly without limitation, to image registration in medical diagnostic systems.

~~In current clinical practice, it is not uncommon that several medical images are~~
to be compared or combined. For example, this occurs when images of a single individual are
5 acquired by different techniques, each producing different information about the individual.
One technique may depict brain function very well and another a brain tumour.

The combination of the two is crucial in determining whether the tumour can
be resected without damaging vital brain areas. A second example is that of images of an
individual taken over a period of time. This can be used, among other things, to study the
10 development of anatomical structures. Besides the comparison of images of a single
individual, comparisons of images of different individuals is also performed, e.g. to study the
differences and similarities between groups.

To be able to compare images, the contents of the images must be in
alignment. This is often not the case for numerous reasons, such as movement of the
15 individual or differences in the field of view (the part of the anatomy that is captured in the
images). The process of finding the correspondence between the contents of images is called
image registration. This is achieved by optimizing a measure of similarity between images,
such as the position of corresponding landmarks or the similarity in intensity of
corresponding anatomical structures.

20 In most cases, global translations and rotations suffice to align images. When
one image has to be deformed, however, to fit the contents of the other this is referred to as
non-rigid or elastic registration. This is necessary for registration of images of different
individuals (who have different anatomies) or images of a single individual when an
anatomical change has taken place.

25 Various image registration techniques are known from the prior art, such as
from WO 01/ 01346 A1, EP 1 184 802 A2, US 2002 / 0 141 626 A1, US 6,266,453 B1.

The book "Medical Image Registration" by Josef Hajnal provides an overview of the various prior art image registration techniques. As far as elastic image registration is concerned the article "Elastic Image Registration and Pathology Detection" by Paul Thompson and Arthur W. Toga

5 (http://www.loni.ucla.edu/~thompson/PDF/no_pics_ElasChpt.pdf) provides an overview of the known approaches for elastic image registration. This article is also published as a book chapter in "Handbook of Medical Image Processing", Academic Press, 2000.

10 A common disadvantage of prior art image registration methods is the lack of an objective quality criterion. So far, the only reliable way to check the results of the image registration is visual assessment by a human observer. This is a practical problem that substantially limits the application of registration methods. For example, in case of time series where many sequential images have to be registered it is impractical to interrupt an otherwise automatic pre-processing method. This is also true if registration is part of a pre-processing chain.

15

It is therefore an object of the present invention to provide for an improved method of image registration which addresses the problems of the prior art. It is a further object of the present invention to provide for an improved computer program product and
20 improved medical image data processing apparatus for image registration.

The present invention provides for an improved method of image registration where registrations are performed for a number of sub-volumes of the image to be registered in addition to a global registration. For example, a number of sub-volumes contained in the image data is selected manually by an operator by marking the sub-volumes of interest.

25 For this purpose a graphical user interface (GUI) can be utilized. Alternatively or in addition an automatic image segmentation can be performed for identification of such sub-volumes. For example, each of the sub-volumes contains a certain medical region of interest, such as an organ or a tumour.

30 In accordance with the present invention a registration is performed for each one of the sub-volumes in addition to a global registration of the image data. This enables to identify an outlier sub-volume which substantially deviates from the transformation of the other sub-volumes and the global registration. Such an outlier sub-volume can be cut off in order to improve the overall registration result or it can trigger a subsequent elastic

registration for improved registration. The transformation parameter set obtained in the first registration step can be used as an input parameter set for the subsequent elastic registration.

The present invention is particularly advantageous as it registers sub-volumes of the images and translates the registration results to global transformations. In particular
5 this enables a comparison of the resulting transformations which indicates:

- the accuracy of the global transformation, e.g. by measuring variations,
- the reason for the inaccuracy, e.g. too much constraint transformation,
- the location of the problem in the images, e.g. local image artefacts.

In some applications outliers in the registration of the sub-volumes are likely
-----10 to originate from image artefacts or unequal anatomies in the images such as pathology, especially if the structures can be assumed as rigid, such as the skull. An example is neural-MR where a sub-volume is selected on a tumour that does not exist on the other image. Another example is neural-CT where a sub-volume is selected on image artefacts caused by metal fillings. A possible reaction to this detected origin of inaccuracy can be to signal for
15 user-interaction or to cut-off this section for a more accurate global registration.

If the image is to be registered e.g. in the abdomen with the deforming organs such as the liver an additional processing step is performed for improved registration rather than cutting-off the corresponding sub-volume. An inaccurately registered sub-volume can be caused by deformation of the organ, e.g. due to breathing motion, which cannot be
20 appropriately dealt with by a rigid, global transformation. In this case a refinement and / or localization of the transformation is performed in order to improve the registration of this sub-volume. For this improved registration the transformation can be locally extended with more degrees of freedom; in particular non-rigid or elastic image registration can be used for this purpose.

25 Another advantageous application of the present invention is the detection of artefacts in MR inter-leaved scans, i.e. the even and odd slices being not aligned. Image interpolation between the slices results in double edges and other artefacts which make registration inaccurate and can result in a low quality after the reformatting which is subsequent to the registration. The present invention enables to detect such artefacts in order
30 to warn a user that artefacts are present in the MR inter-leaved scans.

In essence, the invention provides for a sub-regional registration to be performed alongside the global registration of the full images. Sub-regions or sub-volumes, of the images to be registered are selected and are registered throughout the sequence of images. In accordance with a preferred embodiment a table of registration information is

compiled for all sub-regions and the global registration containing translation and rotation information. Quantification of the registration process is therefore possible over sub-regions and allows identification of inaccuracies within the overall registration process.

5 In particular, this enables to draw the users attention to the sub-volume or sub-volumes of the global image where the registration process has failed and manual orientation is required. Alternatively the result of the registration method of the invention can be incorporated into a fully automated image handling sequence which enables spurious sections of the sequence of images to be removed.

10 In the following preferred embodiments of the invention are explained in greater detail by making reference to the drawings in which:

Fig. 1 is illustrative of a flow diagram of an embodiment of a method of the invention,

15 Fig. 2 is a schematic example for the registration of sub-volumes,

Fig. 3 is a block diagram of a medical image data acquisition and processing system.

20 Fig. 1 shows a flow diagram of an embodiment of the registration method of the invention. In step 100 image data is provided by an imaging modality. Depending on the application all of the image data are provided by the same image modality. Alternatively the image data of different image modalities are to be combined. For example, X-ray imaging, magnetic resonance imaging (MRI), computer tomography (CT) imaging, functional MRI (fMRI), single photon emission computer tomography (SPECT) or positron emission tomography (PET) are used as image modalities.

25 In step 102 a selection of sub-volumes S_i in the image data is performed. This can be done manually by marking the sub-volumes S_i on a display or by performing an image segmentation step or another suitable image processing step for identification of sub-regions or sub-volumes in the image data.

30 In step 104 image registrations are performed locally for the selected sub-volumes S_i . For example, these registrations are performed by means of a rigid image registration method. In step 106 a parameter set T_i is outputted for each one of the sub-volumes S_i for which a registration has been performed. Each one of the transformation

parameter sets T_i is descriptive of the displacement of the corresponding sub-volume S_i in the two images to be registered.

In step 108 a global registration is performed for the images to be registered.

Again a rigid image registration method can be employed for this purpose. In step 110 a

5 global transformation parameter set T_G is outputted. The global transformation parameter set T_G is descriptive of the displacement of the images to be registered with respect to each other.

In step 112 the index i is initialized to be equal to one.

10 In step 114 a mean distance measure is calculated for the transformation parameter set T_i . This can be done by calculating a distance measure between the transformation-parameter-set T_i and each one of the other transformation parameter-sets T_j and to the global transformation parameter set T_G and calculating a mean value on the basis of these individual distance measures. For this purpose any distance measure for the determination of the distance between two parameter sets or vectors can be used, such as Euclid's distance. For example Euclid's distance is calculated for all pairs of parameter sets
15 T_i, T_j , where $i \neq j$, and the resulting Euclid's distances are added. This provides the mean distance measure.

In step 116 it is determined whether the mean distance measure of step 114 is above a threshold level. If this is not the case the registration of the corresponding sub-volume S_i is deemed to be sufficiently accurate and the control goes to step 120 to increment
20 the index i .

If the mean distance measure is above the threshold the control goes from step 116 to step 118. In step 118 an output signal is generated for identification of the sub-volume S_i . This output signal can be outputted as a warning signal by means of a graphical user interface in order to warn an operator that the registration of the sub-volume S_i is inaccurate.
25 Alternatively or in addition the output signal generated in step 118 triggers the execution of an additional non-rigid, elastic image registration procedure for improved registration of the sub-volume S_i and / or for improved global registration.

As an alternative to steps 114 and 116 another statistical method can be used to identify an outlier parameter set and corresponding sub-volume.

30 Fig. 2 shows a schematic example. The example is illustrative of an application in two dimensions for convenience of explanation. It is to be noted that the example can be extended to more dimensions.

Image 100 is a slice or "slab" of image data which has been acquired by medical image data acquisition. Image 100 is located in the XY-plane 104. Image 102 is also within plane 104 and needs to be registered with image 100.

Image 100 contains the sub-volumes A, B, C and D. These sub-volumes are selected by marking the corresponding regions in image 100 by means of a graphical user interface by an operator and / or by a segmentation step or another suitable data processing step for identification of such regions of interest. Image 102 has corresponding sub-volumes A', B', C' and D'.

An image registration is performed both globally for images 100 and 102 and for the individual sub-volumes. This means that the sub-volumes A and A' are registered as well as the sub-volumes B-B', C-C' and D-D'.

Table 106 of Fig. 2 shows the resulting transformation parameter sets. In the example considered here the transformation parameter set for each individual image registration contains the amount of displacement in the X and Y directions within plane 104 as well as the amount of angular transformation in degrees of rotation.

From table 106 it is apparent that the transformation parameter set for the registration of the sub-volume B-B' substantially deviates from the other transformation parameter sets. The sub-volume B-B' is therefore identified as an outlier. In response a corresponding warning signal is outputted and / or an elastic registration procedure is triggered for improved registration of the sub-volume B-B'. The fact that the transformation parameter set of the sub-volume B-B' is an outlier can be determined by processing table 106 by means of suitable statistical methods and / or by calculating of distance measures.

Fig. 3 shows a block diagram of a computer 200 which is coupled to a medical image data acquisition apparatus 202. Computer 200 has memory 204 for the storage of image data and has a graphical user interface 206. Further computer 200 has segmentation program module 208, image registration program module 210, elastic image registration program module 212 and memory 214 for the storage of transformation parameters (cf. table 106 of Fig. 2). In addition computer 200 has program 216 for controlling the operation of these various components. Computer 200 is coupled to display 218 for rendering of image data. Alternatively or in addition computer 200 is connected to a printer.

In operation the image data is loaded into memory 204 from image data acquisition apparatus 202. The image data is rendered on display 218. By means of graphical user interface 206 an operator can select a number of sub-volumes in the image data.

Alternatively or in addition sub-volumes are selected automatically by means of segmentation program module 208.

- Image registrations are performed by means of program module 210 for registering of the sub-volumes and for performing a global image registration. The
- 5 corresponding transformation parameters are stored in memory 214 for analysis by program 216. When program 216 identifies an outlier sub-volume a warning message is generated and outputted on display 218. Alternatively or in addition program 216 triggers program module 212 for performing an elastic image registration for the outlier sub-volume.

LIST OF REFERENCE NUMBERS:

	100	image
	102	image
	104	plane
	106	table
5	200	computer
	202	image data acquisition apparatus
	204	memory
	206	GUI
	208	segmentation program module
10	210	program module
	212	program module
	214	memory
	216	program
	218	display

CLAIMS:

EPO - DG 1

13. 01. 2003

(94)

1. A method of image registration comprising the steps of:
 - providing at least first image data and second image data,
 - selecting of sub-volumes of the first and the second image data,
 - performing a registration for each one of the sub-volumes, each registration
 - 5 providing a transformation parameter set,
 - performing a global registration for the first and second image data, the global registration providing a global transformation parameter set,
 - comparing one of the transformation parameter sets to other transformation parameter sets and/or to the global transformation parameter set for identification of an
 - 10 outlier transformation parameter set of the transformation parameter sets,
 - outputting of a signal being indicative of the sub-volume of the outlier transformation parameter set.
 2. The method of claim 1, whereby the first image data and / or the second image
 - 15 data is provided by X-ray imaging, magnetic resonance imaging, computer tomography imaging, functional MRI, single photon emission computer tomography or positron emission tomography.
-
3. The method of claim 1 or 2, whereby the selection of the sub-volumes is
 - 20 performed manually by means of a graphical user interface.
 4. The method of claim 1, 2 or 3, whereby the selection of the sub-volumes is performed by means of an image segmentation step.
 - 25 5. The method of anyone of the preceding claims 1 to 4, further comprising calculating a mean distance measure of the one of the transformation parameter sets to the other transformation parameter sets and to the global transformation parameter set, whereby the comparison of the one of the transformation parameter sets with the other transformation parameter sets and the global transformation parameter set is performed on the basis of the

mean distance measure for determining whether the one of the transformation parameter sets is an outlier transformation parameter set.

6. The method of claim 5, whereby the one of the transformation parameter sets is identified as an outlier transformation parameter set, if the mean distance measure of the one of the transformation parameter sets is greater than a threshold distance value.

7. The method of anyone of the preceding claims 1 to 5, further comprising cutting off of the sub-volume of the outlier transformation parameter set.

8. The method of anyone of the preceding claims 1 to 7, further comprising performing an elastic image registration in response to the signal.

9. Computer program product, in particular digital storage medium, comprising program means for registration of at least first image data and second data, the program means being adapted to perform the steps of:

- storing of a selection of sub-volumes of the first and second image data,
- performing a registration for each one of the sub-volumes, each registration providing a transformation parameter set,
- performing a global registration for the first and second image data, the global registration providing a global transformation parameter set,
- comparing one of the transformation parameter sets to other transformation parameter sets and/or to the global transformation parameter set for identification of an outlier transformation parameter set of the transformation parameter sets,
- outputting of a signal being indicative of the sub-volume of the outlier transformation parameter set.

10. A medical image data processing apparatus comprising:

- a memory for a storage of at least first and second image data,
- means for selecting of sub-volumes of the first and second image data,
- means for performing a registration for each one of the sub-volumes and for a global registration of the first and second image data, each registration providing a transformation parameter set,

- means for identification of an outlier transformation parameter set of the transformation parameter sets on the basis of the transformation parameter sets,
- means for outputting of a signal being indicative of the sub-volume of an identified outlier transformation parameter set.

5

11. The medical image data processing apparatus of claim 10, further comprising a graphical user interface for selection of the sub-volumes.

12. The medical image data processing apparatus of claims 10 or 11, further comprising means for image segmentation for the selection of the sub-volumes.

10

13. The medical image data processing apparatus of claims 10, 11 or 12, further comprising means for elastic image registration for performing of an elastic image registration when an outlier transformation parameter set has been identified.

ABSTRACT:

EPO - DG 1

13. 01. 2003

(94)

The present invention relates to a method of image registration comprising the steps of:

- providing at least first image data and second image data;
- selecting of sub-volumes of the first and the second image data,
- 5 - performing a registration for each one of the sub-volumes, each registration providing a transformation parameter set,
- performing a global registration for the first and second image data, the global registration providing a global transformation parameter set,
- comparing one of the transformation parameter sets to other transformation
- 10 parameter sets and/or to the global transformation parameter set for identification of an outlier transformation parameter set of the transformation parameter sets,
- outputting of a signal being indicative of the sub-volume of the outlier transformation parameter set.

15 Fig. 1

13. 01. 2003

1/3

94







FIG. 1



Example:

sub-volume	Translation X	Translation Y	Rotation
A - A'	3.2	1.4	1.5
B - B'	5.1	3.4	3.5
C - C'	3.1	1.4	1.6
D - D'	3.2	1.5	1.5
Global - global'	3.9	1.9	1.7

FIG. 2

3/3





FIG. 3

This Page Blank (uspto)

PCT Application

IB0305898



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.